



HomeGuard Support Products

Build with HomeGuard for total termite protection from day one.

The HomeGuard Precision Termite Management System is a range of building products that are homogeneously impregnated with Bifenthrin, a leading termiticide. The sheeting products are a patented single layer, extruded polymer that provides termite protection for the design life of the building when installed according to the label.

Most HomeGuard products are made from high quality polymers that are designed to withstand the rigours of construction whilst being completely non-invasive, non-leaching and environmentally friendly.

The HomeGuard Precision Termite Management System is registered with the Australian Pesticides & Veterinary Medicines Authority (APVMA). The HomeGuard Termite Management System is deemed to satisfy requirements of the Building Code of Australia Volume One and Volume Two where subterranean termites are known to present a potential risk of attack to buildings (refer to the CodeMark certificate of conformity). HomeGuard Precision Termite Management products are also certified and registered with the Singapore Green Building Council as a SGBC product.

HomeGuard support products solve all installation challenges.

The HomeGuard support products, GT, Protectacote and Termiflex, help ensure full protection of building structures. They can be used to fill building cavities and voids, protect awkward places and all joints and gaps. Using the HomeGuard support products in conjunction with HomeGuard Sheeting and Collars ensures total protection for buildings from subterranean termites.

HomeGuard GT



HomeGuard GT provides total termite protection for the buildings perimeter cavities and voids.

HomeGuard GT is a plastic granular material termite protection product impregnated with Bifenthrin and is designed to prevent concealed entry of subterranean termites through perimeter cavities and construction voids. HomeGuard GT in combination with a strip shield of HomeGuard PB are used as components of a termite management system and meet the requirements of AS 3660.1 and AS 3660.3 - Termite Management.

Directions for Use

Restrains: DO NOT use for remedial treatment of pre-existing termite damage.

Pest	Situations	Rate	Critical Comments
Subterranean Termites	Perimeter cavities and construction voids	Fill perimeter cavity or void to minimum 40 mm depth	For specific details on installation see general instructions below

NOT TO BE USED FOR ANY PURPOSE, OR IN ANY MANNER, CONTRARY TO THIS LABEL UNLESS AUTHORISED UNDER APPROPRIATE LEGISLATION.

See label and installation manual for full details.

Product Description

HomeGuard GT are small black polymer beads. HomeGuard GT is available in 27 L bags.

HomeGuard Protectacote



HomeGuard Protectacote and Primer provide total termite protection for awkward places.

HomeGuard Protectacote is a high impact, acrylic polymer latex, and termiticidal paint product which contains Bifenthrin. It is approved in accordance with AS 3660.1 and AS 3660.3 – Termite Management. The purpose of HomeGuard Protectacote paint is to deter termites from gaining concealed access so as to provide whole of building protection.

Directions for Use

All States (Except Tasmania)

Pest	Situations	Rate	Critical Comments
Subterranean Termites	Pre-construction and post-construction termite protection and water proof barrier for domestic, commercial and industrial buildings and other slab-on-ground structures	In conjunction with other termite and water proofing products, a single layer of HomeGuard Protectacote forms a waterproof and termite resistant barrier	HomeGuard Protectacote is one component of the HomeGuard Precision Termite Management System. It may be installed with other termite and water proofing products, to form a complete and continuous barrier Concrete slab must be constructed in accordance with AS 2870.1
	Waterproofing and termite proofing back-filled walls	1.3 mm minimum dry film	Two liberal coats of HomeGuard Protectacote are required to achieve the minimum thickness required for waterproofing and termite resistance
	Construction joints		
	Posts and poles		

NOT TO BE USED FOR ANY PURPOSE, OR IN ANY MANNER, CONTRARY TO THIS LABEL UNLESS AUTHORISED UNDER APPROPRIATE LEGISLATION.

See label and installation manual for full details.

Product Description

HomeGuard Protectacote is a pale, greyish-blue paint and is available in 15 L buckets.

HomeGuard Termiflex



HomeGuard Termiflex provides total termite protection for all joints and gaps.

HomeGuard Termiflex is a high impact termiticidal adhesive and sealant which contains Bifenthrin. It is to be used with components of the HomeGuard system for precision termite management to ensure whole of building protection for the design life of a building. HomeGuard Termiflex is approved in accordance with AS 3660.1 and AS 3660.3 – Termite Management.

Directions for Use

Restrains: DO NOT use for remedial treatment of pre-existing termite infestations.

Pest	Situations	Rate	Critical Comments
Subterranean Termites except <i>Mastotermes darwinensis</i>	Domestic, commercial, and industrial structures - approved to be used in conjunction with HomeGuard sheet products to form a bond to join sheets together. Also to adhere HomeGuard sheet products to other structural components (eg. timber, concrete, tiles, steel etc.). Can be used in various situations where by a termiticidal sealant/adhesive will assist in the prevention of concealed termite entry into a structure	A single continuous bead applied between two surfaces will create a bond (and/or seal) with termiticidal activity when used in accordance with product instructions	Application of the adhesive/sealant as per the below steps can assist in the management of termites by preventing termites passing through a gap completely and continuously sealed using this product 1. Surface must be clean, dry, free from dust, loose particles and soap residues. If required, clean with turps 2. Cut cartridge tip at 45° from 4-6 mm in diameter 3. Apply firmly onto surface or into joint by pushing sealant ahead of nozzle, making a thick continuous bead 4. If necessary, smooth sealant immediately with tool dipped in turps Refer to the HomeGuard Product Manual for further installation instructions

NOT TO BE USED FOR ANY PURPOSE, OR IN ANY MANNER, CONTRARY TO THIS LABEL UNLESS AUTHORISED UNDER APPROPRIATE LEGISLATION.

See label and installation manual for full details.

Product Description

HomeGuard Termiflex is a clear sealant and is available in 520 g tubes for use with standard 'sausage' guns and nozzles.

Find out more at www.FMCaustralasia.com.au

HomeGuard and the HomeGuard logo are trademarks of FMC Corporation. Copyright© 2017 FMC Australasia Pty Ltd